

# TRUXOR Oil spill cleaning



**Doro Skimmer DS 800** is a combi-skimmer that works mobile and in shallow waters from approximately 0.8 in. water depth. When oil spill have been contained with oil booms, the boom can be attached to the skimmer. This keeps the machine from driving in the oil spill. The gables of the Doro Skimmer can be disassembled, this increases the capacity if the oil is thicker.

<b>Doro Skimmer DS 800</b>	Combined with Salarollpump.
<b>Capacity:</b>	88 GPM (thick oil)
<b>Weight:</b>	136.7 lb
<b>Art. No.</b>	<b>79-5000</b>



**Doro Skimmer** has a holder to place the suction pipe (Salarollpump).



**The Doro skimmer** can be used with or without Salarollpump. The Doro skimmer holds approx. 5.3 gal



**Salarollpump** is a suitable pump for decontamination operations of thick-flowing and polluted media in difficult-to-reach places. The suction pipe can be placed in the Doroskimmer or be used manually. Salarollpump can either suck or pump just by changing the rotation of the pump, e.g. useful when the Doro tank is to be emptied. A strong vacuum gives good suction performance. The high pressure makes it possible to transport the media long distances. Salarollpump can be used separately with a suction pipe or in combination with the Doroskimmer DS 800.

**Capacity:** 53 GPM  
**Weight:** 271.2 lb  
**Working pressure:** 87 PSI  
**Max. pressure:** 130.5 PSI  
**Technical vacuum:** -13.8 PSI  
**Salarollpump Art. no:** 79-3000

**Salarollpump accessories:**

For oil spill clean up: suction pipe, 13.1 ft  
suction tube 2.56 in, 4 quick-couplings  
Ø 2.56 in, 7.4 ft pressure tube 2.56 in, 1  
frame bracket.

**Art. no:** 79-3002

Flat tubing 3"/76 mm delivered in lengths  
of 54.68 yd

**Art. no:** 78-11876

Coupling, female **Art. no:** 78-562676,  
Coupling, male **Art. no:** 78-564676,  
Hose clip 2.95 in **Art. no.:** 01-30474



## Doro tank

The prerequisites for oil spill clean-up vary depending on different environments. During the final phase of the work, there is usually a smaller area of oil where it may be practical to use a mobile tank. The Dorotank is mounted between the pontoons and has connections for easy attachment to the Salarollpump. The Salarollpump is used to empty the tank by pumping the oil via the suction hose.



**Volume:** 52.8gal  
**Weight:** 50.7 lb  
**Art No.** 79-6000

The Dorotank is used in combination with the Doro Skimmer 800.



## Doro Spreader DM 1000

With the DM 1000 oil absorbents are applied easily to oil spills on land or on water. The amount of absorbent being delivered by the rotating spreader head is regulated from the driving seat. The central divider can reduce the application width. Doro spreader DM1000 can be used with most types of absorbents.



**Weight** 147.7 lb  
**Load volume:** 267 gal  
**Max load weight:** 396 lb  
**L:** 3 ft  
**W:** 6.6 ft  
**H:** 2.6 ft  
**Art. No.** 79-15700

RETAILER:

**MEGATOR**  
 Pumping & Pollution Control Solutions

1721 Main Street, Pittsburgh, PA 15215, USA  
 Tel: 412 963-9200 / Fax: 412 963-9214  
 Email: info@megator.com  
 Website: www.megator.com



MANUFACTURING/SALES:  
 Dorotea Mekaniska AB  
 Östra Polarvägen 10  
 917 32 Dorotea  
 +46 942-258 80  
 www.doroteamekaniska.se